



HIKVISION



رد استار الکترونیک








نشانی: تهران - خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶

وب سایت: www.redstar-cctv.com

فاکس: ۶۶۷۳۲۴۳۷

تلفن تماس: ۶۶۷۲۲۱۵۶-۶۶۷۲۴۵۵۶







Turbo HD Camera

No.	Model	Appearance	Description	Price
WDR HD 1080p Camera				
1080P				
1	DS-2CE16D5T-IR		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6mm Lens	call
2	DS-2CE56D5T-IRM		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	call
3	DS-2CE56D5T-IT3		HD1080p,2MP CMOS Sensor, 1 pcs EXIR LED, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6/8/12/16mm Lens	call
4	DS-2CE56D5T-VFIT3		HD1080p,2MP CMOS Sensor, 1 pcs EXIR LED, 50m IR, Outdoor EXIR Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Lens	call
6	DS-2CE56D5T-IR3Z		HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Motorized Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Lens	call
7	DS-2CE16D1T-IR		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), DWDR, IP66, 2.8/3.6/6mm Lens	call
8	DS-2CE56D1T-IR		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	call








Turbo HD Camera







No.	Model	Appearance	Description	Price
WDR HD 1080p Camera				
1080P				
9	DS-2CE16D1T-VFIR3		HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Lens	3.860.000 IRR
10	DS-2CE56D1T-VFIR3		HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Lens	3.800.000 IRR
11	DS-2CE56D1T-IR3Z		HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Motorized Vari-focal Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Motorized Vari-focal Lens	call
1080p Entry Level Series				
1080P				
12	DS-2CE16D0T-IR		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	1.790.000 IRR
13	DS-2CE56D0T-IR		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	1.670.000 IRR
14	DS-2CE56D0T-IRM		HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	1.790.000 IRR

Turbo HD Camera

No.	Model	Appearance	Description	Price
1080p Entry Level Series				
1080P				
15	DS-2CE16D0T-IT1		HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	2.120.000 IRR
16	DS-2CE16D0T-IT3		HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	2.290.000 IRR
17	DS-2CE16D0T-IT5		HD1080p,2MP CMOS Sensor, 4 pcs EXIR LEDs, 80m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	2.630.000 IRR
18	DS-2CE56D0T-IT1		HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	2.120.000 IRR
19	DS-2CE56D0T-IT3		HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	2.290.000 IRR
720p Turbo HD Series				
720P				
20	DS-2CE16C5T-VFIR3		HD720p,1.3MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Bullet, ICR, Low Light, 0.001 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), Digital WDR, IP66, 2.8~12mm Lens	call
21	DS-2CE56C5T-VFIT3		HD720p,1.3MP CMOS Sensor, 1 pcs EXIR LED, 50m IR, Outdoor EXIR Vari-focal Eyeball, ICR, Low Light, 0.001 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), Digital WDR, IP66, 2.8~12mm Lens	call
22	DS-2CE16C2T-VFIR3		HD720p,1MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8~12mm Lens	3.030.000 IRR
23	DS-2CE56C2T-VFIR3		HD720p,1MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8~12mm Lens	3.030.000 IRR



Turbo HD Camera

No.	Model	Appearance	Description	Price
720p Turbo HD Series				
720P				
24	DS-2CE56C0T-IRMM		HD720p,1MP CMOS Sensor, 12 pcs IR LEDs, 20m IR, Indoor IR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, Wide operating temperature range (-40°~60°), 2.8/3.6/6mm Lens	1.160.000 IRR
25	DS-2CE16C0T-IR		HD720p,1MP CMOS Sensor, 24 pcs IR LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6mm Lens	1.400.000 IRR
26	DS-2CE56C0T-IR		HD720p,1MP CMOS Sensor, 24 pcs IR LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6mm Lens	1.280.000 IRR
27	DS-2CE56C0T-IRM		HD720p,1MP CMOS Sensor, 24 pcs IR LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6mm Lens	1.400.000 IRR
28	DS-2CE16C0T-IT1		HD720p,1MP CMOS Sensor, 1 pcs EXIR LED, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6/8mm Lens	1.670.000 IRR
29	DS-2CE16C0T-IT3		HD720p,1MP CMOS Sensor, 1 pcs EXIR LED, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6/8/12/16mm Lens	1.910.000 IRR
30	DS-2CE16C0T-IT5		HD720p,1MP CMOS Sensor, 2 pcs EXIR LEDs, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 3.6/6/8/12/16mm Lens	2.080.000 IRR
31	DS-2CE56C0T-IT1		HD720p,1MP CMOS Sensor, 1 pcs EXIR LED, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6/8mm Lens	1.670.000 IRR
32	DS-2CE56C0T-IT3		HD720p,1MP CMOS Sensor, 1 pcs EXIR LED, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Wide operating temperature range (-40°~60°), 2.8/3.6/6/8mm Lens	1.910.000 IRR
Tester				
33	DS-TT-X41		7" LCD Screen, Support HDTV camera, Up the Coax, 12 VDC output	14.570.000 IRR




No.	Model	Appearance	Description	Price
3MP EXIR Turbo HD Series				
3MP				
34	DS-2CE16F1T-IT		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	2.700.000 IRR
35	DS-2CE56F1T-ITM		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	2.700.000 IRR
36	DS-2CE16F1T-IT1		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	3.020.000 IRR
37	DS-2CE16F1T-IT3		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	3.200.000 IRR
38	DS-2CE16F1T-IT5		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	3.580.000 IRR
39	DS-2CE56F1T-IT1		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	2.890.000 IRR
40	DS-2CE56F1T-IT3		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	3.140.000 IRR
41	DS-2CE16F7T-IT3Z		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Lens	7.590.000 IRR
42	DS-2CE56F7T-IT3Z		3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Lens	6.780.000 IRR

Turbo HD Camera



No.	Model	Appearance	Description	Price
1080p High Level Series				
1080P				
43	DS-2CE16D7T-IT		HD1080p,2MP CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	2.610.000 IRR
44	DS-2CE56D7T-ITM		HD1080p,2MP CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	2.610.000 IRR
45	DS-2CE16D7T-IT1		HD1080p,2MP CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	2.910.000 IRR
46	DS-2CE16D7T-IT3		HD1080p,2MP CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6/8/12/16mm Lens	3.090.000 IRR
47	DS-2CE16D7T-IT5		HD1080p,2MP CMOS Sensor, EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6/8/12/16mm Lens	3.460.000 IRR
48	DS-2CE56D7T-IT1		HD1080p,2MP CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	2.790.000 IRR
49	DS-2CE56D7T-IT3		HD1080p,2MP CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6/8/12/16mm Lens	3.030.000 IRR
50	DS-2CE16D7T-IT3Z		HD1080p,2MP CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Lens	5.150.000 IRR
51	DS-2CE56D7T-IT3Z		HD1080p,2MP CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Lens	5.030.000 IRR

No.	Model	Appearance	Description	Price
2 Line Series				
1	DS-2CD2020F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE	4.750.000 IRR
2	DS-2CD2022WD-I		1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	5.750.000 IRR
3	DS-2CD2042WD-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	6.400.000 IRR
4	DS-2CD2052-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+ Optimized Codec	7.880.000 IRR
5	DS-2CD2120F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage	4.750.000 IRR
6	DS-2CD2120F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), -S: Audio/Alarm I/O connectors	5.160.000 IRR
7	DS-2CD2122FWD-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec	5.750.000 IRR
8	DS-2CD2122FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec/ -S: Audio/Alarm I/O	6.160.000 IRR
9	DS-2CD2142FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm I/O”	6.700.000 IRR
10	DS-2CD2152F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm I/O”	8.300.000 IRR






Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
11	DS-2CD2322WD-I		1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+ Optimized Codec	6.550.000 IRR
12	DS-2CD2342WD-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+	7.230.000 IRR
13	DS-2CD2352-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+	8.710.000 IRR
14	DS-2CD2420F-IW		"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, -W: Built-in Wi-Fi with WPS"	4.750.000 IRR
15	DS-2CD2422FWD-IW		1/2.8" Progressive CMOS, ICR, ICR, 0.01lux/F1.2, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+	5.870.000 IRR
16	DS-2CD2442FWD-IW		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+ Optimized Codec	6.520.000 IRR
17	DS-2CD2520F		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Vandal-proof IK10,	4.510.000 IRR
18	DS-2CD2522FWD-I		"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), H.264+	7.880.000 IRR
19	DS-2CD2542FWD-IS		"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), H.264+-S: Audio/alarm I/O	9.000.000 IRR





Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
20	DS-2CD2620F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),	8.180.000 IRR
21	DS-2CD2620F-IZ		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),-Z:Motorized VF lens”	9.660.000 IRR
22	DS-2CD2622FWD-IS		“1/2.8” Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	11.860.000 IRR
23	DS-2CD2642FWD-IS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	13.520.000 IRR
24	DS-2CD2642FWD-IZS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens”	15.930.000 IRR
25	DS-2CD2652F-IS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+-S: Audio/alarm IO	16.700.000 IRR
26	DS-2CD2652F-IZS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+/-S: Audio/alarm IO/-Z: Motorized VF lens”	18.740.000 IRR
27	DS-2CD2720F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof”	8.470.000 IRR
28	DS-2CD2720F-IZ		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof,-Z:Motorized VF lens”	9.830.000 IRR
29	DS-2CD2722FWD-IS		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO	12.110.000 IRR



Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
30	DS-2CD2742FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+-S: Audio/alarm IO	13.770.000 IRR
31	DS-2CD2742FWD-IZS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+-S: Audio/alarm IO/-Z: Motorized	16.190.000 IRR
32	DS-2CD2752F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO	17.090.000 IRR
33	DS-2CD2752F-IZS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens”	19.000.000 IRR
34	DS-2CD2232-IS		1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 6mm/F2.0 lens (4mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 50m, Bracket included	7.770.000 IRR
35	DS-2CD2332-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	6.933.000 IRR
36	DS-2CD2632F-I		“1/3” Progressive CMOS, ICR, 0.1lux/F1.2, 2048x1536:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Support mobile monitoring via HIK-cloud P2P	10.800.000 IRR
37	DS-2CD2732F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Vandal-proof housing, Support mobile monitoring via HIK-cloud P2P	11.000.000 IRR


Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
38	DS-2CD2T22WD-I3		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -3: 1pcs EXIR LED, up to 30m IR range”	6.900.000 IRR
39	DS-2CD2T22WD-I5		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -5: 2pcs EXIR LEDs, up to 50m IR range	7.210.000 IRR
40	DS-2CD2T42WD-I5		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -15: 2pcs EXIR LEDs, up to 50m IR range	8.040.000 IRR
41	DS-2CD2T52-I5		1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ , 2pcs EXIR LEDs, up to 50m IR range	9.900.000 IRR
42	DS-2CD2942F-IS		“1/3” Progressive CMOS, Electronic Day/night, Up to 2464 x 1520 resolution, 1.6mm/F1.6 fixed lens, 180° Panoramic view, H.264/MJPEG, 3D DNR, DC12V & PoE, Support on-board storage up to 64GB, software de-warping via iVMS5200 or iVMS4200, -I: 3pcs IR LEDs, up to 10m IR/-S: Audio/Alarm IO	16.690.000 IRR
43	DS-2CD2F22FWD-IS		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included),-S: Audio/alarm	7.590.000 IRR
44	DS-2CD2F42FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 1920x1080: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB (SD card not included), Pan:0° ~180°, Tilt: 0°~75°, -S: Audio/Alarm IO	8.420.000 IRR
45	DS-2CD2F52F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, -S: Audio/Alarm IO”	10.430.000 IRR
46	DS-2CD2E20F-W		“1/3” Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Color Lens Cover optional -W: Built-in Wi-Fi”	6.460.000 IRR



Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
47	DS-2CD2Q10FD-IW		1/4" Progressive CMOS, ICR, 0lux with IR, 4mm, Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection,	6.820.000 IRR
48	DS-2CD2D14WD		1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,	5.340.000 IRR


Turbo HD DVR

No.	Model	Appearance	Recording Resolution Supported	SATA Interface	Description	Price
DS-7200 Series Turbo HD DVR						
720P/1080P						
1	DS-7204HQHI-SH		1080P	1	4 Turbo HD/Analog self-adaptive interfaces input, 4-ch video&4-ch audio input, 1 SATA interface,1920×1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, standalone 1U case	call
2	DS-7204HGHI-SH		720P	1	4 Turbo HD/Analog self-adaptive interfaces input, 4-ch video&1-ch audio input, 1 SATA interface,1920×1080P: 12 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, standalone 1U case	call
3	DS-7208HGHI-SH			2	8 Turbo HD/Analog self-adaptive interfaces input, 8-ch video&1-ch audio input, 1 SATA interface,1920×1080P: 12 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, standalone 1U case	call

Turbo HD DVR

No.	Model	Appearance	Recording Resolution Supported	SATA Interface	Description	Price
DS-7200 Series Turbo HD DVR						
720P						
4	DS-7204HGHI-F1 (Turbo HD 3.0)		720P	1	4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1 SATA interface, 1280×720P: 25(P)/30(N) fps/ch, 260 1U case	3.980.000 IRR
5	DS-7208HGHI-F1 (Turbo HD 3.0)				8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 1 SATA interface, 1280×720P: 25(P)/30(N) fps/ch, 260 1U case	6.370.000 IRR
6	DS-7208HGHI-F2 (Turbo HD 3.0)			2	8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2 SATA interfaces, 1280×720P: 25(P)/30(N) fps/ch, 380 1U case	8.520.000 IRR
7	DS-7216HGHI-F2 (Turbo HD 3.0)				16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, 2 SATA interfaces, 1280×720P: 25(P)/30(N) fps/ch, 380 1U case	12.040.000 IRR
720P / 1080P						
8	DS-7204HQHI-F1/N (Turbo HD 3.0)		720P/ 1080P	1	4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1 SATA interface, 1920×1080P: 12 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, support CVBS output, standalone 1U case	call
9	DS-7208HQHI-F1/N (Turbo HD 3.0)				8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 1 SATA interface, 1920×1080P: 10 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, support CVBS output, standalone 1U case	7.790.000 IRR
10	DS-7208HQHI-F2/N (Turbo HD 3.0)			2	8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2 SATA interfaces, 1920×1080P: 10 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, support CVBS output, 380 1U case	8.830.000 IRR
11	DS-7216HQHI-F2/N (Turbo HD 3.0)				16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, 2 SATA interfaces, 1920×1080P: 12 fps/ch, 1280×720P: 25(P)/30(N) fps/ch, 4K UHD output, support CVBS output, 380 1U case	14.750.000 IRR

Turbo HD DVR

No.	Model	Appearance	Recording Resolution Supported	SATA Interface	Description	Price
DS-7200 Series Turbo HD DVR						
1080P / 3MP / 5MP						
12	DS-7204HUHI-F1/N (Turbo HD 3.0)		5MP /3MP /1080P	1	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, 5MP: 12fps, 3MP: 15fps, 1920×1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case	call
13	DS-7208HUHI-F1/N (Turbo HD 3.0)				8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 1 SATA interface, 5MP: 12fps, 3MP: 15fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 8/4, support CVBS output, standalone 1U case	10.900.000 IRR
14	DS-7208HUHI-F2/N (Turbo HD 3.0)				8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interfaces, 5MP: 12fps, 3MP: 15fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 8/4, support CVBS output, 380 1U case	12.300.000 IRR
15	DS-7216HUHI-F2/N (Turbo HD 3.0)				16 Turbo HD/AHD/Analog interface input, 16-ch video&4-ch audio input, 2 SATA interfaces, 5MP: 12fps, 3MP: 15fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 16/4, support CVBS output, 380 1U case	22.320.000 IRR

No.	Model	Appearance	Output Bandwidth	PoE Ports	Decoding Capability	Description	Price
DS-7600 Series NVR							
16	DS-7600NI-E1/A		80Mbps	N/A	6-ch 1080P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, 22 inch monitor	24.580.000 IRR
17	DS-7604NI-E1		80Mbps	N/A	4-ch 1080P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	4.800.000 IRR
18	DS-7604NI-E1/4P			4	4-ch 1080P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	7.070.000 IRR
19	DS-7608NI-E2			N/A	6-ch 1080P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	6.690.000 IRR
20	DS-7608NI-E2/8P				8	6-ch 1080P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case
21	DS-7608NI-K2		160Mbps	N/A	2-ch 4K / 8-ch 1080P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	8.950.000 IRR
22	DS-7616NI-E2		80Mbps	N/A	6-ch 1080P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	7.380.000 IRR
23	DS-7616NI-E2/8P			8		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	11.730.000 IRR
24	DS-7616NI-E2/16P			16		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	15.130.000 IRR

No.	Model	Appearance	Output Bandwidth	PoE Ports	Decoding Capability	Description	Price
DS-7600 Series NVR							
25	DS-7616NI-K2		160Mbps	N/A	2-ch 4K / 8-ch 1080P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	10.090.000 IRR
DS-7700 Series NVR							
26	DS-7716NI-E4		80Mbps	N/A	6-ch 1080P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	14.500.000 IRR
27	DS-7716NI-E4/16P			16		160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	22.320.000 IRR
28	DS-7716NI-K4		160Mbps	N/A	2-ch 4K / 8-ch 1080P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	17.900.000 IRR
29	DS-7732NI-E4		80Mbps	N/A	6-ch 1080P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	18.910.000 IRR
30	DS-7732NI-E4/16P			16		200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	26.720.000 IRR
31	DS-7732NI-K4		160Mbps	N/A	2-ch 4K / 8-ch 1080P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	22.440.000 IRR