











Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
New VF Dome Series									
IPC3234SR-DV		4MP	2.8-12mm, Manual	✓	✓	1/1	120dB WDR H.265 Smart Functions	1/3" CMOS, ICR, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, 120dB WDR, DC12V & PoE, 3D DNR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, BNC output, IP67 & IK10, 2.8-12mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	11,500,000
IPC3234SR3-DVZ28			2.8-12mm, Motorized	✓	✓	1/1		1/3" CMOS, ICR, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, 120dB WDR, DC12V & PoE, 3D DNR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, BNC output, IP67 & IK10, 2.8-12mm Motorized lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	13,500,000
IPC3232ER-VS		2MP	2.8-12mm, Manual	✓	×	×	DWDR 3-Axis IP67&IK10	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, DWDR, Corridor mode, ROI, Micro SD card slot, IP67 & IK10, 2.8-12mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog	7,950,000
IPC3232ER-DVZ28			2.8-12mm, Motorized	✓	✓	1/1	120dB WDR H.265 Smart Functions	1/3" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, 120dB WDR, DC12V & PoE, 3D DNR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, BNC output, IP67 & IK10, 2.8-12mm Motorized lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	10,500,000
Economic VF Bullet Series									
IPC2324EBR-DP		4MP	2.8-12mm, Manual	✓	✓	1/1	120dB WDR H.265 Smart Functions	1/3" CMOS, ICR, 2688 × 1520:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE 3D DNR, DWDR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -30 to 60°C, IP67, IK10, 2.812mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Built-in bracket, دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	11,500,000
IPC2324EBR-DPZ28			2.8-12mm, Motorized	✓	✓	1/1		1/3" CMOS, ICR, 2688 × 1520:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE 3D DNR, DWDR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -30 to 60°C, IP67, IK10, 2.812mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Built-in bracket, دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	13,500,000






تلفن تماس: ۰۶۶۷۲۲۱۵۶ - ۰۶۶۷۲۴۵۵۶ - ۰۶۶۷۳۲۴۳۷ - ۰۶۶۷۴۸۵۲۹

نشانی: خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶

Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
IPC2322EBR-P		2MP	2.8-12mm, Manual	✓	✓	1/1	DWDR, IP67, IK10	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams , DC12V & PoE 3D DNR, DWDR, Corridor mode , ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -30 to 60°C, IP67, IK10 , 2.8-12mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity) , Defog, IR anti-reflection window, Built-in bracket	8,050,000
IPC2322EBR-DPZ28			2.8-12mm, Motorized	✓	✓	1/1	120dB WDR H.265 Smart Functions	1/3" CMOS, ICR, 1920x1080:30fps, H.265 , H.264/MJPEG, Triple streams , DC12V & PoE, 3D DNR, DWDR, Corridor mode , ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -30 to 60°C, IP67, IK10 , 2.812mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity) , Defog, IR anti-reflection window, Built-in bracket , دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	10,500,000
Starview Series									
 IPC322ER3-DUVPF28-B		2MP	2.8mm, Fixed	✓	✓	1/1	120dB WDR IP67&IK10 H.265 Starlight HLC Smart functions	1/2.9" CMOS, ICR, 1920x1080:30fps, H.265 /H.264/MJPEG, Triple streams , DC12V & PoE, Micro SD card slot, 120dB WDR, Alarm in/out 1/1, Audio in/out 2/1, IP67 & IK10 , Fixed lens (2.8mm), IR range: up to 30m, 3-Axis, Starlight: 0.002 Lux min. illumination(Starview) + دارای قابلیت شمارش افراد + تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط - دید در شب رنگی	7,000,000
 IPC322ER3-DUVPF40-B			4mm, Fixed	✓	✓	1/1	120dB WDR IP67&IK10 H.265 Starlight HLC Smart functions	1/2.9" CMOS, ICR, 1920x1080:30fps, H.265 /H.264/MJPEG, Triple streams , DC12V & PoE, Micro SD card slot, 120dB WDR, Alarm in/out 1/1, Audio in/out 2/1, IP67 & IK10 , Fixed lens (4mm), IR range: up to 30m, 3-Axis, Starlight: 0.002 Lux min. illumination(Starview) + دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط دید در شب رنگی	7,000,000
 IPC2122SR3-UPF40		2MP	4mm, Fixed	×	×	×	DWDR IP67 H.265 Starlight HLC Smart functions	1/2.9" CMOS, ICR, 1920x1080:30fps, H.265 /H.264/MJPEG, Triple stream , DC12V & PoE, IP67 , Fixed lens (4mm), IR range: up to 30m. IR anti-reflection window, Built-in bracket. Starlight: 0.002 Lux min. illumination(Starview) دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط دید در شب رنگی	7,000,000

Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
NEW IPC2222SR5-UPF40-B		2MP	4mm, Fixed	✓	×	×	starlight DWDR H.265 Smart Functions 50 m IR Range	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265, H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, DWDR, Corridor Mode, IP66, IK10, Fixed lens(4mm, 6mm optional), IR range: up to 50m, IR antireflection window, Built-in bracket, NAA(Network-auto-adaptivity), Defog, Starlight: 0.002 Lux min. illumination(Starview) دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط دید در شب رنگی	8,500,000
Economic Mini Dome Camera Series									
IPC314SR-DVPF28		4MP	2.8mm, Fixed	✓	✓	1/1	120 dB WDR H.265 Smart Functions Built-in Mic	1/3" CMOS, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -35 to 60°C, IP66 & IK10, Fixed lens(2.8mm, 6mm optional), IR range: up to 30m, NAA(Network-auto-adaptivity), Defog3 دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	7,950,000
IPC314SR-DVPF36			3.6mm, Fixed	✓	✓	1/1	120 dB WDR H.265 Smart Functions Built-in Mic	1/3" CMOS, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -35 to 60°C, IP66 & IK10, Fixed lens(2.8mm, 6mm optional), IR range: up to 30m, NAA(Network-auto-adaptivity), Defog3 دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	7,950,000
Economic Turret Camera Series									
IPC3614SR3-DPF28		4MP	2.8mm, Fixed	×	×	×	120dB WDR H.265 Smart Functions	1/3" CMOS, ICR, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, -30~60°C, IP67, Fixed lens(2.8mm, 3.6mm, 6mm optional), Metal Base, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window M : Metal Basement (Optional) دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	5,750,000
IPC3614SR3-DPF36			3.6mm, Fixed	×	×	×			5,750,000





Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
IPC3612ER3-PF28-B		2MP	2.8mm, Fixed	×	×	×	DWDR H.265 Smart Functions	1/2.7" CMOS, ICR, 1920x1080:30fps, H.265, H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, DWDR, Corridor Mode, -30~60°C, IP67, Fixed lens(2.8mm, 3.6mm, 6mm optional), IR range: up to 30m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window30 دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	4,200,000
Economic Fixed Dome Series									
IPC324ER3-DVPF28		4MP	2.8mm, Fixed	✓	✓	1/1	120dB WDR H.265 Smart Functions	1/3" CMOS, 2592x1520:20fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -35 to 60°C, IP67 & IK10, Fixed lens(2.8mm, 3.6mm, 6mm optional), IR range: up to 30m, NAA(Network-auto-adaptivity), Defog دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	6,100,000
IPC324ER3-DVPF36			3.6mm, Fixed	✓	✓	1/1			6,100,000
IPC322SR3-DVSPF28-B		2MP	2.8mm, Fixed	✓	×	×	120dB WDR H.265 Smart Functions	1/2.9" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, ROI, Micro SD card slot, -35 to 60, IP67 & IK10, Fixed lens 2.8mm, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	4,950,000
IPC322ER3-DVPF28		2MP	2.8mm, Fixed	✓	✓	✓	120dB WDR IP67 & IK10 3-Axis	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, -35 to 60, IP67 & IK10, Fixed lens(2.8mm, 3.6mm, 6mm optional), IR range: up to 30m, NAA(Network-auto-adaptivity), Defog	4,800,000

Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
Economic Bullet Series									
IPC2124SR3-DPF36		4MP	3.6mm, Fixed	×	×	×	120dB WDR IP67, IK10 H.265 Smart Functions	1/3" CMOS, ICR, 2592x1520:20fps, H.265 /H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, IP67, IK10, Fixed lens(3.6mm, 6mm, 12mm optional), IR range: up to 30m, IR anti-reflection window, Built-in bracket, NAA(Network-auto-adaptivity), Defog قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	5,950,000
IPC2122SR3-PF40-B		2MP	4mm, Fixed	×	×	×	DWDR H.265 Smart Functions	1/2.7" CMOS, ICR, 1920x1080:30fps, H.265 , H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, DWDR, Corridor Mode, IP67, IK10, Fixed lens(4mm, 6mm optional), IR range: up to 30m, IR anti-reflection window, Built-in bracket, NAA(Network-auto-adaptivity), Defog قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	3,950,000
IPC222ER-F36		2MP	3.6mm, Fixed	×	✓	1/1	DWDR, IP66 IK10	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, DWDR, Corridor Mode, IP66, IK10, Fixed lens, IR range: up to 30m, IR anti-reflection window, Built-in bracket, NAA(Network-auto-adaptivity), Defog/Audio I/O	5,800,000
NEW IPC2224SR5-DPF40-B		4MP	4mm, Fixed	✓	×	×	120dB WDR IP67&IK10 H.265 HLC Smart functions 50 m IR Range	1/3" CMOS, ICR, 2592*1520: 20fps; 2560*1440: 25fps, H.265 /H.264/MJPEG, Triple streams, DC12V & PoE, IP67&IK10, Fixed lens(4.0mm), IR range: up to 50m, IR anti-reflection window, Built-in bracket دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	7,700,000
Fixed Lens IR PT Camera									
NEW IPC744SR5-PF40-32G		4MP	4mm, Fixed	EMMC, 32G	✓	2/1	Pan&Tilt Camera DWDR H.265 Smart Functions 50 m IR Range	1/3" CMOS, ICR, 2592x1520:20fps, H.265 /H.264/MJPEG, Triple streams, DC12V & PoE, 3D DNR, 120dB WDR, Corridor Mode, IP66, IK10, Fixed lens 4mm, IR range: up to 50m, IR anti-reflection window, Built-in bracket, NAA(Network-auto-adaptivity), Defog, Built-in 32 GB eMMC, Pan Range: 250°, Tilt Range:-50° ~ 50°, Alarm in/out 2/1, Audio, Built-in bracket تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	17,000,000



Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
NEW IPC742SR9-PZ30-32G		2MP	3-6mm optical zoom	EMMC, 32G	✓	2/1	Pan & Tilt Camera DWDR H.265 Smart Functions 100 m IR Range	1/2.8" CMOS, ICR, 1920*1080: 30fps, H.265/H.264/MJPEG , Triple streams, DC12V & PoE, IP66, 3-6mm 2X optical zoom, IR range: up to 100m , IR anti-reflection window, Built-in bracket. 32G EMMC storage. Pan: 250°, Tilt: -50°~50°. 400 presets. دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	17,500,000
Fisheye Camera									
NEW IPC814SR-DVPPF16		4MP	1.6mm, Fixed	✓	✓	1/1	120dB WDR H.265 IP66 & IK10 Built-in Mic	1/3" CMOS, ICR, H.265 , Single stream (180° panoramic), DC 12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 1/1, Audio & Mic, BNC output, IP66 & IK10, 1.6mm fixed lens, IR range: 10m, IR anti-reflection window دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	15,000,000
IPC868ER-VF18		12MP	1.8mm, Fixed	✓	✓	2/1	360° Panoramic, DWDR, IP66&IK10, Speaker & Mic	1/1.7" CMOS, 4000*3000: 20fps, H.264/MJPEG, Quintuple streams , DC12V & PoE, 3D DNR, ROI, Alarm in/out 2/1, IR Range: 20m, build-in speaker & microphone, two-way audio , BNC Output, IP66, IK10, -30 to 60°C, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, BNC Output	Call
Box Camera Series									
IPC542E-DLC		2MP	N/A	✓	✓	2/1	120dB WDR HLC Low light	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams , AC 24V & DC12V & PoE, 120dB WDR, HLC, Corridor Mode , ROI, SD card slot, Alarm in/out 2/1 , Audio, BNC output, Zoom/Focus interface, NAA(Network-auto-adaptivity), Defog	15,000,000
IPC562E-DUG		2MP	N/A	✓	✓	2/1	Starlight Optical Fiber 120dB WDR HLC, ABF, H.265, Optical Defog Smart Functions	1/1.9" CMOS, ICR, 1920x1080:60fps, H.265/H.264/MJPEG , Triple streams, ABF , AC 24V & DC12V & PoE, 120dB WDR , 3D DNR, HLC, Corridor mode , ROI, SD card slot, Alarm in/out 2/1 , Audio, Zoom/Focus interface, SFP Slot+RJ45, Ultra low-light(Starlight), NAA(Network-auto-adaptivity), Optical Defog & Digital Defog, دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	26,000,000
NEW IPC568E-G		12MP	N/A	✓	✓	2/1	12MP, Smart Functions, Optical & Digital Defog, HLC, Optical Fiber	1/1.7" CMOS, ICR, 4000X3000:20fps, 3840X2160:30fps, H.265/H.264/MJPEG , Triple streams, AC 24V&DC12V&PoE, SD card slot, Alarm in/out 2/1, Audio, BNC output, Zoom/Focus interface, SFP Slot+RJ45 , Smart Functions, Optical & Digital Defog , 3D DNR, DWDR, HLC, Corridor mode, ROI دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call

تلفن تماس: ۰۶۶۷۲۲۱۵۶ - ۰۶۶۷۲۴۵۵۶ - ۰۶۶۷۳۲۴۳۷ - ۰۶۶۷۴۸۵۲۹

نشانی: خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶

Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
High End Starlight Series									
NEW IPC3232ER3-DUVZ		2MP	2.8-12mm, Motorized	✓	✓	1/1	Starlight, 120 dB WDR, IP67, IK10, Smart Functions	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, 120dB WDR, DC12V & PoE, 3D DNR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 1/1, Audio, BNC output, IP67 & IK10, 2.8-12mm Motorized lens, IR range: up to 30m, NAA(Network-auto-adaptivity), Defog, Ultra-low-light(Starlight), BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
IPC252ERA-X22DUG		2MP	6.5 ~ 143 mm , X22 Optical Zoom	✓	✓	2/1	200m IR, Starlight, Smart Functions , 120dB WDR, IP67, Optical Fiber,	1/1.9" CMOS, ICR, 1920 x 1080:60fps, H.265/H.264/MJPEG, Triple streams, AC24V, 3D DNR, 120 dB WDR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 2/1, Audio, BNC Output, -40 to 60°C, IP67, IK10, 6.5-143mm 22X Optical Zoom, SFP Slot+RJ45, IR range: up to 200m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Ultra low-light(Starlight), BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
IPC262ER9-DUZ		2MP	2.8-12mm, Motorized	✓	✓	2/1	Starlight, Smart Functions , 120dB WDR, IP67, 100m IR,	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & AC24V & PoE, 3D DNR, 120dB WDR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 2/1, Audio, -40 to 60°C, IP67, IK10, 2.8-12mm Varifocal lens, IR range: up to 100m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Ultra low-light(Starlight), BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
IPC262ER9-X10DU		2MP	4.7 ~ 47mm, 10X Optical Zoom	✓	✓	2/1	Starlight, Smart Functions, 120dB WDR, IP67, 100m IR,	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams, DC12V & AC24V & PoE, 3D DNR, 120dB WDR, Corridor mode, ROI, Micro SD card slot, Alarm in/out 2/1, Audio, -40 to 60°C, IP67, IK10, 4.7-47mm 10X Optical Zoom, IR range: up to 100m, NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Ultra low-light(Starlight), BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call



Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
NEW IPC262EFW-DUZ		2MP	2.8-12mm, 4X Optical Zoom	✓	✓	2/1	White&IR Light, Starlight, Smart Functions, IP67, PIR, 120dB WDR, 50m IR&10m white light	1/2.8" CMOS, ICR, 1920x1080:30fps, H.265/H.264/MJPEG, Triple streams , DC12V& AC24V & PoE, 3D DNR, 120dB WDR, Corridor mode , ROI, Micro SD card slot, Alarm in/out 2/1, Audio, -40 to 60°C, IP67, IK10 , 2.8-12mm Varifocal lens, Built-in PIR Sensor, White Light, up to 10 m, IR range: up to 50m, NAA(Network-auto-adaptivity),Defog, IR anti-reflection window, Ultra low-light(Starlight), BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
4K WDR Ultra-HD Varifocal Dome Camera									
NEW IPC3238ER3-DVZ		8MP	2.8-12mm, 4X optical zoom	✓	✓	1/1	120 dB WDR, IP67, IK10, H.265 Smart Functions	1/2.5" CMOS, ICR, 3840x2160:30fps, H.265/H.264/MJPEG, Triple streams , DC12V& AC24V & PoE, 3D DNR, 120dB WDR, Corridor mode , ROI, Micro SD card slot, Alarm in/out 2/1, Audio, -40 to 60°C, IP67, IK10 , 2.8-12mm Varifocal lens, IR range: up to 30m, NAA(Network-auto-adaptivity),Defog, IR anti-reflection window, BNC output دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
NEW IPC268ER9-DZ		8MP	2.8-12mm, 4X optical zoom	✓	✓	2/1	120dB WDR IP67 H.265 100m IR Smart functions	1/2.5" CMOS, ICR, 4K (3840x2160): 30 fps; 1080P (1920x1080): Max. 30 fps, H.265/H.264/MJPEG, Triple stream , AC 24V & DC12V & PoE, 120dB WDR, Micro SD card slot, Alarm in/out 2/1, Audio, BNC output, IP67, 2.8-12mm Motorized Varifocal lens, 4Xoptical zoom with Auto Focus, IR antireflection window, Built-in bracket. IR range: up to100m. دارای قابلیت شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call


Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
IP Speed Dome Camera									
Economic PTZ Series									
IPC6222ER-X20-B		2MP	20X Optical zoom	✓	✓	1/1	DWDR IP66 H.265 20X optical zoom HLC Smart functions DIS	1/3" CMOS, ICR, 1920x1080:30fps, H.265 /H.264/MJPEG, Triple streams, AC24V/DC24V, Micro SD card slot, Alarm in/out 1/1, Audio, -40-65 , IP66, 20x optical zoom(5.2 ~ 104mm), IR range: up to 150m , IR anti-reflection window	35,000,000
IPC6222ER-X30-B		2MP	30X Optical zoom	✓	✓	1/1	DWDR IP66 H.265 30X optical zoom HLC Smart functions DIS	1/3" CMOS, ICR, 1920x1080:30fps, H.265 /H.264/MJPEG, Triple streams, AC24V/DC24V, Micro SD card slot, Alarm in/out 1/1, Audio, -40-65 , IP66, 30x optical zoom(4.5 ~ 135mm), IR range: up to 150m , IR anti-reflection window	45,000,000
High End PTZ Series									
IPC6242SR-X30		2MP	30X Optical zoom	✓	✓	2/1	DWDR, IP66, IK10, 30x optical zoom	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, AC24V&DC24V, 3D DNR, SD card slot, Alarm in/out 2/1 , Audio, BNC output, -40 to 70°C , IP66, IK10, 30x optical zoom(4.7 ~ 135mm), IR range: up to 150m , NAA(Network-auto-adaptivity), Defog, IR anti-reflection window, Hydrophobic film	Call
IPC6253SR-X33		3MP	33X Optical zoom	✓	✓	2/1	Smart Functions, Auto tracking, 120dB WDR, IP66, 33X Optical zoom, EIS	1/2.8" CMOS, ICR, 2048 × 1520:30fps, H.265 /H.264/MJPEG, Triple streams, AC24V&DC24V, 120dB WDR, 3D DNR, SD card slot, Alarm in/out 2/1 , Audio, BNC output, -40 to 70°C , IP66, IK10, 33x optical zoom(4.5 ~ 148.5 mm), IR range: up to 150m, NAA(Network-auto-adaptivity), Defog, IR antireflection window, Hydrophobic film دارای قابلیت تعقیب هوشمند سوژه، شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call


Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
Featured PTZ Series									
NEW IPC6252SR-X22U		2MP	22X Optical zoom	✓	✓	2/1	Starlight, 120dB WDR, IP66&IK10,EIS, 22X Optical zoom, Smart Functions, Auto tracking, Fiber optional	1/1.9" CMOS, ICR, 1920x1080:60fps,H.265, H.264/MJPEG, Triple streams, AC24V&DC24V, 120dB WDR, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40-70°C, IP66, IK10, 22x optical zoom(4.7 ~ 103.4mm), IR range: up to 200m, NAA(Network-auto-adaptivity),Defog, IR anti-reflection window,Hydrophobic film, Ultra low-light(Starlight) دارای قابلیت تعقیب هوشمند سوژه، شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
IPC6252SFW-X22U		2MP	22X Optical zoom	✓	✓	2/1	White & IR Light LED, Starlight, 120dB WDR, IP66, EIS, 22X Optical zoom, Smart Function, Auto tracking	1/2.8" CMOS, ICR, 1920x1080:60fps,H.265 H.264/MJPEG, Triple streams, AC24V&DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40-70°C, IP66, IK10, 22x optical zoom(4.7 ~ 103.4mm), White Light & IR LED, White Light: 0~30m, IR 30~150m, Ultra low-light(Starlight), NAA(Networkauto-adaptivity),Defog, دارای قابلیت تعقیب هوشمند سوژه، شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
IPC6242SL-X33		2MP	33X Optical zoom	✓	✓	2/1	120dBWDR, IR laser & LED, EIS,IP66, 33X Optical zoom, Smart Functions, Auto tracking	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, AC24V&DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40-70°C, IP66, IK10, 33x optical zoom(4.5 ~ 148.5mm), Varifocal IR laser, IR range: up to 500m, IR anti-reflection window,Hydrophobic film ,NAA(Network-auto-adaptivity),Defog, دارای قابلیت تعقیب هوشمند سوژه	Call
NEW IPC6242SR-X33G-IA		2MP	33X Optical zoom	✓	✓	2/1	Auto tracking, DWDR, IP66, IK10, 33x optical zoom SFP Slot+RJ45	1/2.8" CMOS, ICR, 1920x1080:30fps, H.264/MJPEG, Triple streams, AC24V&DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40-70°C, IP66, IK10, 33x optical zoom(4.5 ~ 148.5mm), snapshot when a moving object breaks the rule, SFP Slot+RJ45, IR range: up to 150m, IR antireflection window,Hydrophobic film ,NAA(Network-auto-adaptivity),Defog دارای قابلیت تعقیب هوشمند سوژه، شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call
NEW IPC6852SR-X44U		2MP	44X Optical zoom	✓	✓	2/1	Starlight, 120dB WDR, IP66, EIS, 44X Optical zoom, Smart Functions, Auto tracking	1/2.8" CMOS, ICR, 1920X1080:60fps, H.265/H.264/MJPEG, Triple streams, AC24V/DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, IP66, 44x optical zoom(5 ~ 220mm), Starlight, IR range: up to 250m, IR anti-reflection window, Hydrophobic film, 120dB WDR, 3D DNR, ROI, Optical&Digital Defog, -45-70°C, دارای قابلیت تعقیب هوشمند سوژه، شمارش افراد، تشخیص چهره، تشخیص ورود به ناحیه غیر مجاز، تشخیص عبور از خط	Call


تلفن تماس: ۰۶۶۷۲۲۱۵۶ - ۰۶۶۷۲۴۵۵۶ - ۰۶۶۷۳۲۴۳۷ - ۰۶۶۷۴۸۵۲۹




نشانی: خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶





Model Name	Appearance	Resolution	LENS	SD Card	Audio	Alarm I/O	Features	Description	Price
 IPC6248SR-X22		12MP	22x	✓	✓	2/1	12MP, IP66, IK10, 22X optical zoom	1/1.7" CMOS, ICR, 12 MP (4000×3000):20fps,4K (3840×2160):30fps, H.264/MJPEG, Triple streams, AC24V/DC24V, SD card slot, Alarm in/out 2/1, Audio, BNC output, -40-70°C, IP66, IK10, 22x optical zoom(6.5 ~ 143mm), IR range: up to 150m, IR anti-reflection window,Hydrophobic film,NAA(Network-auto-adaptivity),Defog	Call

Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR201 E Series										
NVR201-04E		4-ch/40Mbps	8x720P@25 4 x 1080P@25 2 x 4MP@20	Up to 6MP	1	N/A	N/A	1 x RJ45 1000M	4-ch Synchronous Playback, Video Out: 96Mbps ,Max Online User: 16, 1 SATA HDDs, 1-HDMI/1-VGA output, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	3,350,000
NVR201-08E		8-ch/80Mbps	8x720P@25 4 x 1080P@25 2 x 4MP@20	Up to 6MP	1	N/A	N/A	1 x RJ45 1000M	8-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 1 SATA HDDs, 1-HDMI/1-VGA output, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	4,800,000
NVR201-04EP		4-ch/40Mbps	4 x 1080P@30 2 x 4MP@20	Up to 6MP	1	4 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	4-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 1 SATA HDDs, 1-HDMI/1-VGA output, 4PoE, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	5,900,000

Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR202 E Series										
NVR202-08E		8-ch/80Mbps	8x720P@25 4 x 1080P@30 2 x 4MP@20	Up to 6MP	2	N/A	N/A	1 x RJ45 1000M	8-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 2 SATA HDDs, 1-HDMI/1-VGA output, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	5,550,000
NVR202-16E		16-ch/160Mbps	32xD1 16 x 720P@25 6 x 1080P@25 4 x 4MP@20	Up to 4K	2	N/A	N/A	1 x RJ45 1000M	16-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 2 SATA HDDs,1-HDMI/1-VGA output, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	6,700,000
NVR202-08EP		8-ch/80Mbps	16 x 720P@25 6 x 1080P@25 4 x 4MP@20	Up to 4K	2	8 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	8-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 2 SATA HDDs,1-HDMI/1-VGA output, 8 PoE, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	9,500,000
NVR202-16EP		16-ch/160Mbps	16 x 720P@25 6 x 1080P@25 4 x 4MP@20	Up to 4K	2	8 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	16-ch Synchronous Playback, Video Out: 96Mbps, Max Online User: 16, 2 SATA HDDs,1-HDMI/1-VGA output, 8 PoE, 1 USB 2.0,1 USB 3.0,JBOD, -10°C to 55°C (14°F to 131°F), Mini 1U, 1 x GE, Accurate retrieval, instant playback, Touch Panel	11,000,000





Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR301 Series										
NVR301-04E		4-ch/40Mbps	16x D1 8x 720@25 4 x 1080P@25 3 x 4MP@20 1 x 4K@30	Up to 4K	1	N/A	N/A	1 x RJ45 100M	Support H.265, 4-ch Synchronous Playback, Video Out: 64Mbps, Max Online User: 16, 1 SATA HDDs,1-HDMI/1-VGA output, 2 USB 2.0,JBOD,Mini 1U, -10°C to 55°C (14°F to 131°F), 1 x 100M, Alarm I/O:4/1 , Accurate retrieval, instant playback	4,390,000
NVR301-08E		8-ch/60Mbps	16x D1 8x 720@25 4 x 1080P@25 3 x 4MP@20 1 x 4K@30	Up to 4K	1	N/A	N/A	1 x RJ45 100M	Support H.265, 8-ch Synchronous Playback, Video Out: 64Mbps, Max Online User: 16, 1 SATA HDDs,1-HDMI/1-VGA output, 2 USB 2.0,JBOD,Mini 1U -10°C to 55°C (14°F to 131°F), 1 x 100M, Alarm I/O:4/1 , Accurate retrieval, instant playback	5,950,000
NVR301-08-P8		8-ch/60Mbps	16x D1 8x 720@25 4 x 1080P@25 3 x 4MP@20 1 x 4K@30	Up to 4K	1	8 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 100M	Support H.265, 8-ch Synchronous Playback, Video Out: 64Mbps, Max Online User: 16, 1 SATA HDDs,1-HDMI/1-VGA output, 2 USB 2.0,JBOD,Mini 1U -10°C to 55°C (14°F to 131°F), 1 x 100M, Alarm I/O:4/1 , Accurate retrieval, instant playback	11,000,000


Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR302 Series										
NVR302-08E-P8		8-ch/80Mbps	16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x 12MP@20	Up to 12MP	2	8 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	support H.265, 8-ch Synchronous Playback, Plug & Play, 2 SATA HDDs,1-HDMI/1-VGA output, Rear panel: 1 x USB3.0, Front panel : 1XUSB2.0, JBOD, 1U, 8 POE, -10°C to 55°C (14°F to 131°F), 1 x 1000M, Alarm I/O:4/1, Accurate retrieval, instant playback	16,000,000
NVR302-16E-P8		16-ch/160Mbps	16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x 12MP@20	Up to 12MP	2	8 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	support H.265, 16-ch Synchronous Playback, Plug & Play, 2 SATA HDDs,1-HDMI/1-VGA output, Rear panel: 1 x USB3.0, Front panel : 1XUSB2.0, JBOD, 1U, 16 POE, -10°C to 55°C (14°F to 131°F), 1 x 1000M, Alarm I/O:4/1, Accurate retrieval, instant playback	20,000,000
NVR302-16E-P16		16-ch/160Mbps	16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x 12MP@20	Up to 12MP	2	16 (IEEE802.3at) (Long Distance PoE , Up To 300M)	N/A	1 x RJ45 1000M	support H.265, 16-ch Synchronous Playback, Plug & Play, 2 SATA HDDs,1-HDMI/1-VGA output, Rear panel: 1 x USB3.0, Front panel : 1XUSB2.0, JBOD, 1U, 16 POE, -10°C to 55°C (14°F to 131°F), 1 x 1000M, Alarm I/O:4/1, Accurate retrieval, instant playback	24,000,000







Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR304 Series										
NVR304-16E		16-ch/160Mbps	32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	4	N/A	N/A	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 48/320M, Max Online User: 16, 4 SATA HDDs, 2HDMI/1-VGA output, 2 USB 2.0, 1 USB 3.0, JBOD, -10°C to 55°C (14°F to 131°F), 1U, 2 x GE, Alarm I/O: 16/4, 1 x RS-232, 1 x RS-485 Serial Interface, Accurate retrieval, instant playback	17,000,000
NVR304-32E		32-ch/320Mbps	32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	4	N/A	N/A	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 64/320M, Max Online User: 16, 4 SATA HDDs, 2-HDMI/1-VGA output, 2 USB 2.0, 1 USB 3.0, JBOD, -10°C to 55°C (14°F to 131°F), 1U, 2 x GE, Alarm I/O: 16/4, 1 x RS-232, 1 x RS-485 Serial Interface, Accurate retrieval, instant playback	25,000,000
NVR304-16EP		16-ch/160Mbps	32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	4	16 (IEEE802.3at) (Long Distance PoE, Up To 300M)	N/A	1 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 48/320M, Max Online User: 16, 4 SATA HDDs, 2HDMI/1-VGA output, 2 USB 2.0, 1 USB 3.0, JBOD, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O: 16/4, 1 x RS-232, 1 x RS-485 Serial Interface, Accurate retrieval, instant playback	22,500,000
NVR304-32EP		32-ch/320Mbps	32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	4	16 (IEEE802.3at) (Long Distance PoE, Up To 300M)	N/A	1 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 64/320M, Max Online User: 16, 4 SATA HDDs, 2HDMI/1-VGA output, 2 USB 2.0, 1 USB 3.0, JBOD, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O: 16/4, 1 x RS-485 Serial Interface, 1 x RS-232, Accurate retrieval, instant playback	31,000,000

تلفن تماس: ۰۶۶۷۲۲۱۵۶ - ۰۶۶۷۲۴۵۵۶ - ۰۶۶۷۳۲۴۳۷ - ۰۶۶۷۴۸۵۲۹

نشانی: خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶






Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR308 Series										
NVR308-32E		32-ch/320Mbps	64 xD1 32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	8	N/A	RAID 1,5	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 64/320M, Max Online User: 16, 8 SATA HDDs, Hot Swap, JBOD, RAID1,5, 2-HDMI/1-VGA output, 2 USB 2.0, 1 USB 3.0, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O:16/4, 1 x RS-232, 1 xRS485 Serial Interface, Accurate retrieval, instant playback	Call
NVR308-64E		64-ch/320Mbps	64 xD1 32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	8	N/A	RAID 1,5	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 96/320M, Max Online User: 16, 8 SATA HDDs, Hot Swap, JBOD, RAID 1,5,2-HDMI/1-VGA output, 2 USB 2.0,1 USB 3.0, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O:16/4, 1 x RS-232, 1 xRS485 Serial Interface, Accurate retrieval, instant playback	Call
NVR308-32R		32-ch/320Mbps	64 xD1 32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	8	N/A	RAID 1,5	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 96/320M, Max Online User: 128, 8 SATA HDDs, Support RAID1,5, JBOD, Hot Swap, 2-HDMI/1-VGA output, 2 USB 2.0,1 USB 3.0, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O:16/4, 1 x RS-232, 1 x RS-485 Serial Interface, Accurate retrieval, instant playback, Wireless mouse included	Call
NVR308-64R		64-ch/320Mbps	64 xD1 32 X720p@25 16 x 1080P@25 8 x 4MP@20 4 x 4K@30 4 x12MP@20	Up to 12MP	8	N/A	RAID 1,5	2 x RJ45 1000M	Support H.265, 16-ch Synchronous Playback, Video Out: 128/320M, Max Online User: 128, 8 SATA HDDs, Support RAID1,5, JBOD, Hot Swap, 2-HDMI/1-VGA output, 2 USB 2.0,1 USB 3.0, -10°C to 55°C (14°F to 131°F), 2U, 2 x GE, Alarm I/O:16/4, 1 x RS-232, 1 x RS-485 Serial Interface, Accurate retrieval, instant playback, Wireless mouse included	Call













Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
NVR516 Series										
NVR516-64		64-ch/384Mbps	64 x D1 36 x 720P@30 16 x 1080P@30 4 x 4K@30 4 x 12MP@20 (Decoding Board Optional)	Up to 12MP	16	N/A	RAID 1,5	4 x RJ45 1000M 2 x SFP 1000M	Support H.265 , 16-ch Synchronous Playback, Video Out: 96/384M, Max Online User: 128, 16 SATA HDDs, Up to 48 with Disk Expansion ,Hot Swap, JBOD, RAID 1,5 , 2-HDMI/1-VGA output, (Decoding Board Optional up to 12 HDMI), 4 USB 3.0,-10°C to 55°C (14°F to 131°F), 3U, 4 x GE, 2X SFP GE, Alarm I/O:24/8 ,1 x RS-232, 1 xRS-485 Serial Interface, Redundant Power Supply , Accurate retrieval, instant playback	Call
NVR516-128		128-ch/512Mbps	64 x D1 36 x 720P@30 16 x 1080P@30 4 x 4K@30 4 x 12MP@20 (Decoding Board Optional)	Up to 12MP	16	N/A	RAID 1,5	4 x RJ45 1000M 2 x SFP 1000M	Support H.265 , 16-ch Synchronous Playback, Video Out: 128/384M, Max Online User: 128, 16 SATA HDDs, Up to 48 with Disk Expansion, Hot Swap ,JBOD, RAID 1,5 , 2-HDMI/1-VGA output, (Decoding Board Optional up to 12 HDMI), 4 USB 3.0,-10°C to 55°C (14°F to 131°F), 3U, 4 x GE, 2X SFP GE, Alarm I/O:24/8 ,1 x RS-232, 1 xRS-485 Serial Interface, Redundant Power Supply , Accurate retrieval, instant playback	Call



Model Name	Appearance	Video Input	Capacity	Resolution	SATA	PoE ports	RAID	Network interface	Description	Price
All-In-One Series										
Unicorn		128-ch/ 512Mbps	64 x D1 36 x 720P@30 16 x 1080P@30 4 x 4K@30 (Decoding Board Optional)	Up to 4K	16 (Up to 48 with Expansion)	N/A	RAID 1,5	4 x RJ45 1000M 2 x SFP 1000M	Embedded System Design, Redundant Power Supply, Dual-OS Design, Hot Swap, JBOD, RAID 1,5, 512M Incoming Bandwidth, 1000 Device Connections, Up to 2000 Channels, Support H.265, 4K, Standard ONVIF, 2-HDMI/1-VGA output, 16 SATA HDDs, Up to 48 with Disk Expansion (288T), 4 x GE, 2X SFP GE, Network Fault Tolerance, Multi-IP configuration Unified Management of NVR, IPC, decoder, Support Device Configuration Import/Export Live View, Playback, and Sequence on Video Wall, Two-way Audio, E-map, Real-time Alarm, Alarm plan, HTTPS/SSL Certificate Creation and Upload, 802.1x Authentication, ARP Protection, 4 USB3.0, Up to 1000 Users, B/S, C/S and Mobile App Clients, Screen Splicing, Video Decoding and Display on Video Wall	Call
Extending Device										
DEU1008-IN		N/A	N/A	N/A	8	N/A	RAID 1,5	N/A	2U 8 HDDs Mini SAS Disk Enclosure	Call
DEU1016		N/A	N/A	N/A	16	N/A	RAID 1,5	N/A	3U 16 HDDs Mini SAS Disk Enclosure	Call
FB-HDMI4-C-NB		N/A	64x720P 32 x 1080P 16 x 4MP 8 x 4K	N/A	N/A	N/A	N/A	N/A	4-HDMI decoding card, H.265&4K	Call
FB-HDMI6-C-NB		N/A	96 x 720P 48 x 1080P 24 x 4MP 12 x 4K	N/A	N/A	N/A	N/A	N/A	6-HDMI decoding card, H.265&4K	Call
PWR-300A-IN		N/A	N/A	N/A	N/A	N/A	N/A	N/A	Redundant Power Supply	Call

تلفن تماس: ۰۶۶۷۲۲۱۵۶ - ۰۶۶۷۲۴۵۵۶ - ۰۶۶۷۳۲۴۳۷ - ۰۶۶۷۴۸۵۲۹

نشانی: خیابان جمهوری - بعد از پل حافظ - مرکز تجاری امجد - طبقه همکف - شماره ۶

Model	Picture	Video Input/output	Capacity	Description	Price
Encoder					
DVS4104		4-ch	Video Input: 4-ch / 960H	4 BNC Video Input,H.264,2 RJ45 10M/100M adaptive Ethernet Interface, 1 100Mbps EPON sub card(optional), 2 1000Base-Fx SFP(optional), Audio I/O:4/1, Alarm I/O:4/2, -10°C to 60°C	Call
DVS4116		16-ch	Video Input: 16-ch / 960H	16 BNC Video Input,H.264,2 RJ45 10M/100M/1000m adaptive Ethernet Interface, Audio I/O:16/1, Alarm I/O:8/2, -10°C to 55°C	Call
Decoder					
DC4301		1-ch Video Output	Decoding: 4 x D1 or 1 x 1080P@30	Video output:1-ch,VGA, HDMI or HD-SDI by sub card (optional),2 RJ45 10M/100M/1000M adaptive Ethernet Interface, Audio I/O:1/1, Alarm I/O:2/2, -10°C to 55°C	Call
DC4304		4-ch Video Output	Decoding: 36 x D1 or 8 x 1080P@30	Video ouput:4-ch DVI-I, Video input: 1-ch,HDMI and 1-ch,VGA, 2 RJ45 10M/100M/1000M adaptive Ethernet Interface, Audio I/O:1/8, Alarm I/O:8/6, -10°C to 55°C	Call
DC4308		8-ch Video Output	Decoding: 72 x D1 or 16 x 1080P@30	Video output: 8-ch DVI-I, Video input: 1-ch,HDMI and 1-ch,VGA, 2 RJ45 10M/100M/1000M adaptive Ethernet Interface, Audio I/O:1/8, Alarm I/O:8/6, -10°C to 55°C	Call

Model	Appearance	Compatible with	Mount	Material	Dimensions	Weight	Price
Bracket							
TR-WM04-IN		IPC323x series 	Wall mount	Aluminum	208mmx125mmx125mm (8.2" x 4.9" x 4.9")	0.48kg(1.1lb)	490,000
TR-WM03-IN		IPC36xx series 	Wall mount	Aluminum	188mmx126mmx126mm (7.4" x 5" x 5")	0.44kg(0.97lb)	490,000
TR-CE45-IN		IPC64x Series IPC62xx Series    	Pendent mount (200 mm)	Aluminum	Φ116.5mmx239mm (Φ4.6" x 9.4")	0.67kg(1.5lb)	950,000
TR-WE45-A-IN			Wall mount	Aluminum	216mmx141mmx314mm (8.5" x 5.6" x 12.4")	1.0kg(2.2lb)	1,100,000
TR-UP08-B-IN (Al Alloy)			Vertical Pole mount (Need TR-WE45-IN)	Aluminum	215mmx170mmx52mm (4.7" x 4.7" x 2.1")	1.47kg(3.2lb)	900,000
TR-UC08-B-IN (Al Alloy)			Corner mount (Need TR-WE45-IN)	Aluminum	215mmx210mmx122mm (8.5" x 8.3" x 4.8")	1.87kg(4.1lb)	1,100,000

Model	Appearance	Focal Length	Mount	Format	Pixel	Aperture	Angle of view	Dimensions	Price
Megapixel VF Lens									
LENS-YM0312D-3M-IN		3-12mm	CS	1/2.7"	3MP	DC-Iris, F1.4	105.6°-28.4°	Φ29.0×44.2×43.5	1,550,000
LENS-YM0860D-3M-IN		8-60mm	CS	1/2.5"	3MP	DC-Iris, F1.8	43°-5.6°	Φ39×89	3,950,000