



# PRICE LIST

---

1401 . 12 . 16

SUPPORTED BY  
**REDX**  
www.redka.ir

01



**IPC-B112-PF28**

#### 2.0MP Fixed Bullet Network Camera

- ◆Sensor: 1/2.9" progressive scan, CMOS
- ◆Lens: 2.8mm@F2.1, Angle of view: 107.8°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps; 720P (1280\*720)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆IR Range: UP to 30m
- ◆Ingress Protection: IP67 / Plastic



**25.700.000 IR/rials**

موجودی استعلام شود

02



**IPC-B122-APF40**

#### 2.0MP Fixed Bullet Network Camera, Built-in MIC

- ◆Sensor: 1/2.8" progressive scan, CMOS
- ◆Lens: 4.0mm@F2.1, Angle of view: 87.5°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps; 720P (1280\*720)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆Built in MIC
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆IR Range: UP to 30m
- ◆Ingress Protection: IP67 / Plastic, POE



**29.000.000 IR/rials**

03



**IPC-D112-PF28**

#### 2.0MP Fixed Dome Network Camera

- ◆Sensor: 1/2.9", 2.0 MP, CMOS
- ◆Lens: 2.8mm@F2.0, Angle of view: 107.8°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps; 720P (1280\*720)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, 2AXIS, ONVIF
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆IR Range: UP to 30m
- ◆Ingress Protection: IP67 / Plastic, Vandal Resistant: IK10, POE



**23.700.000 IR/rials**

04



**IPC-D122-PF28**

#### 2.0MP Fixed Dome Network Camera

- ◆Sensor: 1/2.8", Progressive Scan, CMOS
- ◆Lens: 2.8mm@F2.1, Angle of view: 106.7°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps; 720P (1280\*720)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, 2AXIS, ONVIF
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆IR Range: UP to 30m
- ◆Ingress Protection: IP67 / Plastic, Vandal Resistant: IK10, POE



**29.000.000 IR/rials**

05



**IPC-T122-APF28**

#### 2.0MP Fixed Turret Network Camera

- ◆Sensor: 1/2.8" progressive scan, CMOS
- ◆Lens: 2.8mm@F2.1, Angle of view: 106.7°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps; 720P (1280\*720)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, 3-AXIS, ONVIF
- ◆Built in MIC
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆IR Range: UP to 30m
- ◆Ingress Protection: IP67 / Plastic, POE



**29.000.000 IR/rials**

موجودی استعلام شود

06



IPC-B323-APF40

### 3.0MP Smart White Light Bullet Network Camera

- ◆ Sensor: 1/2.7", 3.0 Megapixel, CMOS
- ◆ Lens: 4.0mm @F1.6, Angle of view: 86.5°
- ◆ Ultra 265, H.265, H.264
- ◆ Frame Rate: Main Stream: 3MP(2304\*1290), Max 25fps; 1080P (1920\*1080), Max 30fps; 720P(1280\*720)
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ Behavior Detection: Motion detection, Human body detection, Audio detection
- ◆ Built in MIC, Built in Speaker
- ◆ White Light Range: Up to 30m (98ft) White light range
- ◆ Smart IR, IR Range: UP to 50m
- ◆ Ingress Protection: IP67/ Plastic, POE



37.000.000 IR/rials

موجودی استعلام شود

07



IPC-B213-APF40W

### 3.0MP HD Fixed Dual-light Bullet Network Camera

- ◆ Sensor: 1/2.8", 3.0 Megapixel, CMOS
- ◆ Lens: 4.0mm @F2.0, Angle of view: 89.0°
- ◆ Ultra 265, H.265, H.264, U-Code
- ◆ Frame Rate: Main Stream: 3MP(2304\*1290), Max 25fps; 1080P (1920\*1080), Max 30fps; 720P(1280\*720)
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ Basic Detection: Motion detection, Human body detection, Audio detection
- ◆ Built in MIC
- ◆ White Light Range: Up to 30m (98ft) White light range
- ◆ Smart IR, IR Range: UP to 50m
- ◆ Ingress Protection: IP67/ Plastic, With Bracket



41.300.000 IR/rials

موجودی استعلام شود

08



IPC-B114-PF28

### 4.0MP Fixed Bullet Network Camera

- ◆ Sensor: 1/2.7", progrssive scan, CMOS
- ◆ Lens: 2.8mm @F2.1, Angle of view: 112.7°
- ◆ Ultra 265, H.265, H.264, MJPEG
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 1080P (1920\*1080), Max 20fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: UP to 30m
- ◆ Ingress Protection: IP67/ Plastic, POE



41.000.000 IR/rials

موجودی استعلام شود

09



IPC-B124-APF40

### 4.0MP Fixed Bullet Network Camera

- ◆ Sensor: 1/3", progrssive scan, CMOS
- ◆ Lens: 4.0mm @F2.1, Angle of view: 79.0°
- ◆ Ultra 265, H.265, H.264
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 1080P (1920\*1080), Max 20fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ Built in MIC
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: UP to 30m
- ◆ Ingress Protection: IP67/ Plastic, POE



44.000.000 IR/rials

10



IPC-D114-PF28

### 4.0MP Fixed Dome Network Camera

- ◆ Sensor: 1/2.7", progrssive scan, CMOS
- ◆ Lens: 2.8mm @F2.0, Angle of view: 112.7°
- ◆ Ultra 265, H.265, H.264, MJPEG
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 1080P (1920\*1080), Max 20fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: UP to 30m
- ◆ Ingress Protection: IP67/ Plastic, Vandal Resistant: IK10, POE



32.000.000 IR/rials

11



**IPC-D124-PF28**

#### 4.0MP Fixed Dome Network Camera

- ◆Sensor: 1/3" progressive scan, CMOS
- ◆Lens: 2.8mm @F2.1, Angle of view: 97°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 3MP(2304\*1296), Max 20fps; 1080P(1920\*1080), Max 30fps
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR, IR Range: UP to 30m
- ◆Ingress Protection: IP67/ Plastic, Vandal Resistant: IK10, POE



**37.000.000 IR/rials**

موجودی استعلام شود

12



**IPC-T124-APF28**

#### 4.0MP Fixed Turret Network Camera

- ◆Sensor: 1/3" progressive scan, CMOS
- ◆Lens: 2.8mm @F2.1, Angle of view: 97°
- ◆Ultra 265, H.265, H.264
- ◆Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 3MP(2304\*1296), Max 20fps; 1080P(1920\*1080), Max 30fps
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, 3-Axis, ONVIF
- ◆Built in MIC
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR, IR Range: UP to 30m
- ◆Ingress Protection: IP67/ Plastic, POE



**43.000.000 IR/rials**

13



**IPC-B314-APKZ**

#### 4.0MP HD VF Bullet Network Camera

- ◆Sensor: 1/2.7" progressive scan, CMOS
- ◆Lens: 2.8 ~ 12mm @F1.8, Angle of view: 102.79° ~ 30.86°
- ◆Ultra 265, H.265, H.264, MJPEG
- ◆Frame Rate: Main Stream: 4MP(2560\*1440), Max 25fps; 3MP(2304\*1296), Max 30fps; 1080P(1920\*1080), Max 30fps
- ◆Digital Defog, WDR120db, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆Behavior Detection: motion detection, tampering alarm, audio detection, human body detection
- ◆Built in MIC, Reset Button
- ◆Edge Storage: Micro SD, up to 256GB, ANR
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR, IR Range: UP to 50m ◆Ingress Protection: IP67/ Plastic, POE



**86.000.000 IR/rials**

14



**IPC-B314-PKZ**

#### 4.0MP VF IR Bullet Network Camera

- ◆Sensor: 1/3" progressive scan, CMOS
- ◆Lens: 2.8 ~ 12mm @F1.6, Angle of view: 91.0° ~ 27°
- ◆Ultra 265, H.265, H.264, MJPEG
- ◆Frame Rate: Main Stream: 4MP(2560\*1440)
- ◆Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆White Balance: Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
- ◆Edge Storage: Micro SD, up to 256GB, ANR
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR, IR Range: UP to 30m
- ◆Ingress Protection: IP67/ Plastic, POE



**79.000.000 IR/rials**

موجودی استعلام شود

15



**IPC-D314-APKZ**

#### 4.0MP VF Vandal-resistand IR Network Dome Camera

- ◆Sensor: 1/2.7" progressive scan, CMOS
- ◆Lens: 2.8 ~ 12mm @F1.8, Angle of view: 102.79° ~ 30.86°
- ◆Ultra 265, H.265, H.264, MJPEG
- ◆Frame Rate: Main Stream: 4MP(2560\*1440), Max 25fps; 3MP(2304\*1296), Max 25fps; 1080P(1920\*1080), Max 30fps
- ◆Digital Defog, WDR120db, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆Behavior Detection: motion detection, tampering alarm, audio detection, human body detection
- ◆Edge Storage: Micro SD, up to 256GB, ANR ◆Built in MIC, Reset Button
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR, IR Range: UP to 30m
- ◆Ingress Protection: IP67/ Plastic, Vandal Resistant: IK10, POE



**83.000.000 IR/rials**

16



**IPC-D314-PKZ**

#### 4.0MP VF Vandal-resistand IR Dome Network Camera

- ◆Sensor:1/3" progrssive scan,CMOS
- ◆Lens:2.8 ~ 12mm @F1.8, Angle of view: 106.9° ~28.4°
- ◆Ultra 265, H.265, H.264, MJPEG
- ◆Frame Rate: Main Stream:4MP(2560\*1440), Max 20fps;3MP (2304\*1296),Max 25fps 1080P (1920\*1080), Max 30fps
- ◆Digital Defog,DWDR, HLC,BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆White Balance:Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
- ◆Edge Storage:Micro SD, up to 256GB, ANR, Reset Button
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR,IR Range:UP to 30m
- ◆Ingress Protection: IP67/ Plastic,Vandal Resistant:IK10, POE



**79.000.000 IR/rials**

موجودی استعلام شود

17



**IPC-P4P4-X25**

#### 4.0MP 25X Light-hunter Network PTZ Dome Camera

- ◆Sensor:1/2.8" progrssive scan,CMOS
- ◆Lens:4.8 ~ 120mm @F1.5 ~F3.8 , Angle of view: 52.20° ~2.74°
- ◆Min. Illumination: Colour: 0.003 Lux (F1.5, AGC ON) , 0 Lux with IR
- ◆Digital Zoom: 16, Optical Zoom: 25
- ◆Ultra 265, H.265, H.264, MJPEG, U-code
- ◆Frame Rate: Main Stream:4MP(2688\*1520), Max 30fps
- ◆Digital Defog,WDR120db , HLC,BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆Intelligent: Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection, Face Capture, People Counting
- ◆Motion detection, Audio detection, Tampering Alarm, Auto Tracking, Two-way Audio
- ◆Edge Storage:Micro SD, up to 256GB, ANR
- ◆Audio I/O:1 /1, Alarm I/O:2/1, Reset Button
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR,IR Range:UP to 30m
- ◆Ingress Protection: IP67/ Plastic,Vandal Resistant:IK10, POE
- ◆NO BRACKET



**385.000.000 IR/rials**

موجودی استعلام شود

18



**IPC-P1E5-AX4PKC**

#### 5.0MP Light-hunter Active Deterrence Mini PTZ Camera

- ◆Sensor:1/2.7" progrssive scan,CMOS
- ◆Lens:2.8 ~ 12mm @F1.6, Angle of view: 30.6° ~104.1°
- ◆Min. Illumination: Colour:0.003 lux (F1.6,AGC ON) 0 lux with IR
- ◆Ultra 265, H.265, H.264, MJPEG
- ◆Frame Rate: 5MP (2880\*1620), Max 30fps; 4MP (2560\*1440), Max 25fps;3MP (2304\*1296), Max 25fps; 2MP (1920\*1080), Max 30fps;
- ◆Digital Defog,WDR120db , HLC,BLC, OSD, Privacy mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆Intelligent:Cross Line, Intrusion, Enter Area, Leave Area detection;Motion detection
- ◆Motion detection, Tampering alarm, Audio Detection, Two-way Audio
- ◆Edge Storage:Micro SD, up to 256GB, ANR
- ◆Built-in Mic, Built-in Speaker, Alarm Light, Reset Button
- ◆IR anti-reflection window to increase the infrared transmittance
- ◆Smart IR,IR Range:UP to 50m, Warm Light Range to 10m
- ◆Ingress Protection: IP66, POE



**155.000.000 IR/rials**

موجودی استعلام شود

19



**NVR-104E2**

#### 4-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:4-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Front and Rear Panel
- ◆Third-party IP camera supported with ONVIF conformance: Profile S, Profile G, Profile T
- ◆Incoming/Outcoming Bandwith: 64/32Mbps



**48.000.000 IR/rials**

موجودی اعلام شود

20



**NVR-110E2**

#### 10-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:10-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆Audio Output: 1-ch, 3.5mm
- ◆USB Interface :2x Rear Panel
- ◆Third-party IP camera supported with ONVIF conformance: Profile S, Profile G, Profile T
- ◆Incoming/Outcoming Bandwith: 64/32Mbps



**52.500.000 IR/rials**

21



**NVR-116E**

#### 16-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:16-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆Audio Output: 1-ch, 3.5mm
- ◆USB Interface :2x Rear Panel
- ◆Third-party IP camera supported with ONVIF conformance: Profile S, Profile G, Profile T
- ◆Incoming/Outcoming Bandwith: 64/32Mbps



**71.000.000 IR/rials**

22



**NVR-116E2**

#### 16-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:16-ch
- ◆Decoding format: H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆Audio Output: 1-ch, 3.5mm
- ◆USB Interface :2x Rear Panel
- ◆Incoming/Outcoming Bandwith: 64/32Mbps



**67.700.000 IR/rials**

23



**NVR-104E2-P4**

#### 4-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:4-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆POE: 4 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Front and Rear Panel
- ◆Incoming/Outcoming Bandwith:40Mbps



**74.000.000 IR/rials**

24



**NVR-108E2-P8**

#### 8-ch, 1 SATA HDD Network Video Recorder

- ◆IP Video Input:8-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆POE: 8 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Audio Output: 1-ch, RCA
- ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Rear Panel
- ◆Incoming/Outcoming Bandwidth:50/40Mbps



**97.800.000 IR/rials**

25



**NVR-216S-P16**

#### 16-ch, 2 SATA HDDs Network Video Recorder

- ◆IP Video Input:16-ch ◆POE Income:16-ch
- ◆Decoding format: Ultra 265/H/265/H/264
- ◆Recording Resolution:8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆Hard Disk: 2SATAInterface, Up to 10TB
- ◆ANR Technology to enhance the storage reliability when the network is disconnected
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆POE: 16 independent 100Mbps PoE network interfaces
- ◆Audio Output: 1-ch, RCA ◆Support 1-ch HDMI, 1-ch VGA
- ◆Alarm in: 4-ch, Alarm Out:1-ch
- ◆USB Interface :2x Front and Rear Panel
- ◆Incoming/Outcoming Bandwidth:160/96Mbps



**202.000.000 IR/rials**

26



**XVR-104G2**

#### 4-ch, 1 SATA HDD XVR

- ◆Analog Video Input:4-ch,BNC
- ◆IP Video Input:2-ch(only IP up to 6-ch) , each channel up to 4MP
- ◆Decoding format: H/265/H/264
- ◆Support audio over coaxial cable
- ◆Support AHD input: 5MP@12fps/ 1080P@30fps
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Recording Resolution:5MP Lite/ 1080P ◆Play back: 4-ch
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Audio Output: 1-ch, RCA ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Front and Rear Panel
- ◆Incoming/Outcoming Bandwidth:40/50Mbps



**Coming Soon**

27



**XVR-108G2**

#### 8-ch, 1 SATA HDD XVR

- ◆Analog Video Input:8-ch,BNC
- ◆IP Video Input:4-ch(only IP up to 6-ch) , each channel up to 4MP
- ◆Decoding format: H/265/H/264
- ◆Support audio over coaxial cable
- ◆Support AHD input: 5MP@12fps/ 1080P@30fps
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Recording Resolution:5MP Lite/ 1080P ◆Play back: 8-ch
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Audio Output: 1-ch, RCA ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Front and Rear Panel
- ◆Incoming/Outcoming Bandwidth:40/60Mbps



**Coming Soon**

28



**XVR-116G2**

#### 16-ch, 1 SATA HDD XVR

- ◆Analog Video Input:16-ch,BNC
- ◆IP Video Input:8-ch(only IP up to 16-ch) , each channel up to 8MP
- ◆Decoding format: H/265/H/264
- ◆Support audio over coaxial cable
- ◆Support AHD input: 5MP@12fps/ 1080P@30fps
- ◆Hard Disk: 1SATAInterface, Up to 6TB
- ◆Recording Resolution:5MP Lite/ 1080P ◆Play back: 16-ch
- ◆Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆Audio Output: 1-ch, RCA ◆Support 1-ch HDMI, 1-ch VGA
- ◆USB Interface :2x Front and Rear Panel
- ◆Incoming/Outcoming Bandwidth:40/50Mbps



**Coming Soon**