



uniarch

By **uniview**

۳۶ ماه گارانتی ردکا

uniarch products, powered by uniview, guaranteed by redka

www.Redstar-cctv.com



IPC-B323-APF40

Key Features

Sensor: 1/2.7", 3.0 Megapixel, CMOS

Lens: 4.0mm @F1.6

IR Range: Up to 50m

Video Compression: Ultra 265, H.265, H.264

Frame Rate: Main Stream: 3MP (2304*1296), Max 25fps; 1080P (1920*1080), Max 30ps; 1080P (1920*1080), Max 25ps
Sub Stream: 640*360; CIF

Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, Behavior Detection, Build in MIC, Build in Speaker, ONVIF

Ingress Protection: IP65 / Plastic

23.540.000

IR/Rials



IPC-B112-PF28

Key Features

Sensor: 1/2.9", 2.0 Megapixel, CMOS

Lens: 2.8mm @F2.1

IR Range: Up to 30m

Video Compression: Ultra 265, H.265, H.264

Frame Rate: Main Stream: 1080P (1920*1080), Max 25fps; 720P (1280*720), Max 25fps;
Sub Stream: 4CIF (704*576), Max 25fps

Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, ONVIF

Ingress Protection: IP67 / Plastic

14.740.000

IR/Rials



IPC-B114-PF28

Key Features

Sensor: 1/2.7", 4.0 Megapixel, CMOS

Lens: 2.8mm @F2.1

IR Range: Up to 30m

Video Compression: Ultra 265, H.265, H.264, MJPEG

Frame Rate: Main Stream: 4MP (2560*1440), Max 20fps; 1080P (1920*1080), Max 20fps;
Sub Stream: 720P (1280*720), Max 20fps

Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, ONVIF

Ingress Protection: IP67 / Plastic

23.130.000

IR/Rials



IPC-D112-PF28

Key Features

Sensor: 1/2.9", 2.0 Megapixel, CMOS

Lens: 2.8mm @F2.0

IR Range: Up to 30m

Video Compression: Ultra 265, H.265, H.264

Frame Rate: Main Stream: 1080P (1920*1080), Max 25fps; 720P (1280*720), Max 25fps; Sub Stream: 4CIF (704*576), Max 25fps

Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, ONVIF

Ingress Protection: IP67 / Plastic

Vandal Resistant : IK10

14.740.000

IR/Rials



IPC-D114-PF28

Key Features

Sensor: 1/2.7", 4.0 Megapixel, CMOS

Lens: 2.8mm @F2.0

IR Range: Up to 30m

Video Compression: Ultra 265, H.265, H.264, MJPEG

Main Stream: 4MP (2560*1440), Max 20fps; 1080P (1920*1080), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps

Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, ONVIF

Ingress Protection: IP67 / Plastic

Vandal Resistant : IK10

23.130.000

IR/Rials



IPC-D314-KPZ

Key Features

Sensor: 1/3", 4.0 megapixel, progressive scan, CMOS
 Lens: 2.8 ~ 12mm, motorized zoom lens
 Angle of View: 106.9°~28.4°(H), 55.3°~16.4°(V), 138.9°~34.9°(O)
 IR Range: Up to 30m
 Wavelength: 850nm
 Video Compression: Ultra 265, H.265, H.264, MJPEG
 Frame Rate: Main Stream: 4MP (2592*1520), Max 20fps
 Sub Stream: 720P (1280*720), Max 20fps
 Third Stream: D1 (704*576), Max 20fps
 Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, ANR, Motion Detection, API, ONVIF
 Edge Storage: Micro SD, up to 256GB
 Ingress Protection: IP67 / Metal+Plastic
 Vandal Resistant : IK10

51.400.000

IR/Rials



IPC-B314-KPZ

Key Features

Sensor: 1/3", 4.0 megapixel, progressive scan, CMOS
 Lens: 2.8 ~ 12mm, motorized zoom lens
 Angle of View: 91.0°~27°(H), 54.4°~13.7°(V), 118.3°~33.2°(O)
 IR Range: Up to 30m
 Wavelength: 850nm
 Video Compression: Ultra 265, H.265, H.264, MJPEG
 Frame Rate: Main Stream: 4MP (2592*1520), Max 20fps
 Sub Stream: 720P (1280*720), Max 20fps
 Third Stream: D1 (704*576), Max 20fps
 Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, ANR, Motion Detection, API, ONVIF
 Edge Storage: Micro SD, up to 256GB
 Ingress Protection: IP67 / Metal

51.400.000

IR/Rials



NVR-104B

Key Features

IP Video Input: 4-ch
POE Income: 4-ch
Decoding format: Ultra 265 / H. 265 / H.264
Recording Resolution: 1080p/960p/720p/D1/2CIF/CIF
Live view/Playback: 1080p/960p/720p/D1/2CIF/CIF
Hard Disk: 1 SATA Interface, Up to 6TB
Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
Support 1-ch HDMI, 1-ch VGA
USB Interface: 2x Front and Rear Panel
Incoming/Outcoming Bandwidth: 40 Mbps



NVR-108BC

Key Features

IP Video Input: 10-ch
Decoding format: Ultra 265 / H. 265 / H.264
Recording Resolution: 1080p/960p/720p/D1/2CIF/CIF
Live view/Playback: 1080p/960p/720p/D1/2CIF/CIF
Hard Disk: 1 SATA Interface, Up to 6TB
Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
Support 1-ch HDMI, 1-ch VGA
USB Interface: 2x Rear Panel
Incoming/Outcoming Bandwidth: 40 Mbps



NVR-216S-P16

Key Features

IP Video Input: 16-ch
POE Income: 16-ch
Decoding format: Ultra 265 / H. 265 / H.264
Recording Resolution: 8MP / 6MP / 5MP / 4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Live view/Playback: 8MP / 6MP / 5MP / 4MP / 3MP/1080p/960p/720p/D1/2CIF/CIF
Hard Disk: 2 SATA Interface, Up to 10TB for each disk
Network Interface: 1 RJ-45 10M / 100M / 1000M self a daptive Ethernet Interface
Audio Output: 1-ch, RCA
USB Interface: 2x Front and Rear Panel
Incoming/Outcoming Bandwidth: 160/96 Mbps

22.110.000

IR/Rials

15.970.000

IR/Rials

91.750.000

IR/Rials



NVR-110B2

Key Features

IP Video Input: 10-ch
Decoding format: Ultra 265 / H. 265 / H.264
Recording Resolution: 5MP / 4MP / 3MP / 1080P/960P/720P/960H/D1/2CIF/CIF/QCIF
Live view/Playback: 5MP / 4MP / 3MP / 1080P/960P/720P/960H/D1/2CIF/CIF/QCIF
Hard Disk: 1 SATA Interface, Up to 6TB
Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
Support 1-ch HDMI, 1-ch VGA
USB Interface: 2x Rear Panel
Incoming/Outcoming Bandwidth: 40 Mbps



NVR-116E

Key Features

IP Video Input: 16-ch
Decoding format: H.265 / H.264
Recording Resolution: 8MP / 6MP / 5MP / 4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Live view/Playback: 8MP / 6MP / 5MP / 4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Hard Disk: 1 SATA Interface, Up to 6TB
Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
Audio Input: 1-ch
USB Interface: 2x Rear Panel
Incoming/Outcoming Bandwidth: 64/32 Mbps

22.520.000

IR/Rials

38.560.000

IR/Rials